



Timeless natural hues

No 1016424

FRENCH OAK ZENITUDE BOIS FLOTTÉ, DIVA 184 CLICK / 12 MM

Characteristics

Species: French oak **Origin:** France

Grading: Zenitude - light and dark wood, black knots, opened knots, discolouration, cracks, splits, sapwood. Grade with all the peculiarities of the wood without limitation. The size of the knots is proportional to the width of the planks.

Finish: Bois flotté - brushed, matt lacquered with unfinish aspect / Ecostrong lacquer

Design

Engineered extra-wide single plank made under the patent EN 13489
Click system made under Unilin patent No EP1640530



Description

Width: 184 mm
Length: 495 to 1992 mm
Thickness: 12 mm
Top layer: 2.5 mm
Core: HDF*
Counterbalance: unrolled wood
Profile: 4 bevels

*High Density Fiber Board

Packaging

Sqm/pack: 2.20
Pack/pallet: 40
Sqm/pallet: 88
Weight/sqm: 9.9 kg
Weight/pallet: 871.2 kg

Installation method



Glue-free floating installation under the patent DTU 51.11




Glue down installation under the patent DTU 51.2



Floating installation using plastic DPM and Isol 20 or fully glue down using presto PM



Fully glue down using presto PM



*Emissions of volatile substances which could be toxic if inhaled. These are rated on a scale from A+ (very low) to C (high).



Registration, Evaluation, Authorisation of Chemicals.



100% CHÈNE DE FRANCE

DECLARATION OF PERFORMANCE

NO 1016424



Unique identification code of the product-type: Diva 184 Click, 12 mm, French oak

Intended use/es: Engineered extra-wide single plank made under the patent EN 13489

Wood flooring - Multi-layer parquet elements in accordance with the European Standard EN 13489

Manufacturer: PANAGET - 3 rue d'Orgères 35230 Bourgbarré / FRANCE

System/s of Assessment and Verification of Constancy of Performance: No 4

Harmonised standard: EN 14342 : 2013

Declared performances:

Essential features	Performances	Appropriate Technical Documentation and/or Specific Technical Documentation	
Reaction to fire	Dfl-s1	EN 14342 : 2013	
Features for this classification: - Average minimum density (Kg/m ³) - Average thickness (mm) - Intended use, fitting mode	500 12 Floating fit		
Formaldehyde emission	E1		EN 717-1
Content of pentachlorophenol	PCP ≤ 5 ppm		-
Release of other dangerous substances: - VOC* emissions (Decree No 2011-321) - CMR 1&2** emissions (Decree No DEVP0910046A)	Classe A < 1µg/m ³	ISO 16000	
Breaking strength	N/A	-	
Slipperiness	N/A	-	
Thermal conductivity (W/m.K)	0.15	EN 14342 / Chapter 4.7	
Thermal resistance (m ² .K/W)	0.080		
Biological sustainability	Classe 1	EN 335	

N/A: Not Applicable

*VOCs: Volatile Organic Compounds

**CMR 1&2: Carcinogenics, Mutagens or Reproductive toxin of 1 and 2 category

The performance of product identified above is in conformity with the set of declared performance/s. This declaration of performance is issued, in accordance with Regulation (EU) No 305/2011, under the sole responsibility of the manufacturer identified above.

Signed for and behalf of the manufacturer by: Jean-Luc ROY - Chairman

Bourgbarré, 4 January 2019

Jean-Luc ROY

