



Timeless natural hues

# PANAGET

manufacture française de parquet  
DEPUIS 1929



No 1000070

## FRENCH OAK AUTHENTIC TOPAZE, DIVA 184 TONGUE & GROOVE / 14 MM

### Characteristics

**Species:** French oak **Origin:** France

**Grading: Authentic** - light and dark wood, black knots, filled knots, partially opened knots, discolouration, black marks, cracks. The size of the knots is proportional to the width of the planks.

**Finish: Topaze** - brushed, matt lacquered / Ecostrong lacquer

### Design

Engineered extra-wide single plank made under the patent EN 13489  
Tongue & Groove



### Description

**Width:** 184 mm  
**Length:** 500 to 2000 mm  
**Thickness:** 14 mm  
**Top layer:** 3.4 mm  
**Core:** plywood  
**Counterbalance:** unrolled wood  
**Profile:** 4 bevels

### Packaging

**Sqm/pack:** 1.84  
**Pack/pallet:** 44  
**Sqm/pallet:** 80.96  
**Weight/sqm:** 7.4 kg  
**Weight/pallet:** 599.1 kg

### Installation method




Floating glued  
installation under the  
patent DTU 51.11



Glue down installation  
under the patent DTU 51.2



Floating installation using  
plastic DPM and Isol 20 or fully  
glue down using presto PM



\*Emissions of volatile substances which could be toxic if inhaled. These are rated on a scale from A+ (very low) to C (high).



Registration, Evaluation,  
Authorisation of Chemicals.



100% CHÈNE  
DE FRANCE

# DECLARATION OF PERFORMANCE

## NO 1000070



**Unique identification code of the product-type:** Diva 184 Tongue & Groove, 14 mm, French oak

**Intended use/es:** Engineered extra-wide single plank made under the patent EN 13489

Wood flooring - Multi-layer parquet elements in accordance with the European Standard EN 13489

**Manufacturer:** PANAGET - 3 rue d'Orgères 35230 Bourgbarré / FRANCE

**System/s of Assessment and Verification of Constancy of Performance:** No 4

**Harmonised standard:** EN 14342 : 2013

### Declared performances:

Essential features	Performances	Appropriate Technical Documentation and/or Specific Technical Documentation
Reaction to fire	Dfl-s1	EN 14342 : 2013
Features for this classification: - Average minimum density (Kg/m <sup>3</sup> ) - Average thickness (mm) - Intended use, fitting mode	500 14 Floating fit	
Formaldehyde emission	E1	
Content of pentachlorophenol	PCP ≤ 5 ppm	-
Release of other dangerous substances: - VOC* emissions (Decree No 2011-321) - CMR 1&2** emissions (Decree No DEVP0910046A)	Classe A < 1µg/m <sup>3</sup>	ISO 16000
Breaking strength	N/A	-
Slipperiness	N/A	-
Thermal conductivity (W/m.K)	0.13	EN 14342 / Chapter 4.7
Thermal resistance (m <sup>2</sup> .K/W)	0.108	
Biological sustainability	Classe 1	EN 335

N/A: Not Applicable

\*VOCs: Volatile Organic Compounds

\*\*CMR 1&2: Carcinogenics, Mutagens or Reproductive toxin of 1 and 2 category

The performance of product identified above is in conformity with the set of declared performance/s. This declaration of performance is issued, in accordance with Regulation (EU) No 305/2011, under the sole responsibility of the manufacturer identified above.

Signed for and behalf of the manufacturer by: Jean-Luc ROY - Chairman

Bourgbarré, 1st January 2019

Jean-Luc ROY

